



TECHNICAL DATA SHEET

ADIMOK- 292

General


ADIMOK-292 is an excellent general purpose liquid hindered amine light stabilizer especially developed for coatings. Its cost efficiency provides significantly extended life time to coatings by minimizing paint defects such as cracking and gloss loss.

Chemical Name

The active substance is a mixture of :

Bis(1,2,2,6,6-pentamethyl-4-piperidiny)- sebacate and 1-(Methyl)-8-(1,2,2,6,6-pentamethyl-4-piperidiny)- sebacate

Structure



Molecular Weight : 508.8 and 369.6

Physical Properties

Appearance : slightly yellow liquid

Specific density at 20°C : 0.99 g/cm³

Miscibility (g/100 g solution) at 20°C :

Butylcarbitol	> 50	
Butanol	> 50	
Butylacetate	> 50	
Depanol J ¹⁾	> 50	¹⁾ Trade Mark of Hoechst
Ethylglycol	> 50	
1-methoxypropylacetate-2	> 50	
Methylethylketone	> 50	
Solvesso 100 ²⁾	> 50	²⁾ Trade Mark of Esso
Solvesso 150 ²⁾	> 50	
Xylene	> 50	
Water	n.m	n.m= not miscible
Hexanedioldiacrylate	> 50	
Trimethylolpropanetriacrylate	> 50	



The dispersion of ADIMOK-292 in water may be simplified by dilution with a water miscible solvent such as butylcarbitol.

Applications :

- ADIMOK-292 may be used after adequate testing in a broad range of applications such as:
automotive refinish coatings industrial topcoats coil coatings wood stains or trade sales
paints and varnishes radiation curable coatings.
- Its high cost efficiency has been demonstrated in coatings based on a variety of binders such as:
 - one- and two-component polyurethanes
 - thermoplastic acrylics (physical drying)
 - thermosetting acrylics, alkyds and polyesters
 - alkyds (air drying)
 - water borne acrylics
 - phenolics, vinyls
 - radiation curable acrylics
- The weatherability of such coatings can be significantly improved by use of a combination of ADIMOK-292 with a UV absorber, e.g. ADIMOK- 1130, ADIMOK-384, or ADIMOK- 328. These synergistic combinations give automotive coatings superior protection against gloss reduction, cracking, blistering, delamination and color change.
- The light stabilizers may be added in two coat automotive finishes to the base and clear coat. The optimum protection should be determined by evaluating a broad range of concentrations.
- Possible interactions of TINUVIN 292 with paint ingredients such as acid catalysts should be carefully evaluated. Should a negative interaction occur, ADIMOK- 123 would be recommended.
- The optimum additive levels and ratios should be determined from experimental trials covering a range of concentrations.



Recommended Concentrations	Clear coats and	0.5 – 1.0 %	ADIMOK-292
	one coat metallic shades :	+	
		1.0 – 3.0 %	ADIMOK-1130, ADIMOK- 384, ADIMOK-928 or ADIMOK-328
	One coat solid shades :	1.0 – 2.0 %	ADIMOK-292 alone or in Combination with
		1.0 – 3.0 %	ADIMOK-1130, ADIMOK- 384, ADIMOK-928 or ADIMOK-328
Percent by weight of coating resin solids.			

Handling & Safety In accordance with good industrial practice, handle with care and avoid release To the environment. For more detailed information please refer to the material Safety data sheet.

FOR INDUSTRIAL USE ONLY

Important : The following supersedes Buyer's documents. **SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict liability, tort or contract arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled or lab work and must be confirmed by Buyer by testing for its intended conditions of use The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.